

# Fixed Window Series



Tiger Door, LLC has a number of Fixed window products available. Fabricated from heavy walled fiberglass pultrusion profiles, Tiger offers both non-UL fire rated and UL fire rated designs.

The non-UL fire rated constructions available include everything from simple 4-sided to multi-section window wall units. A choice of anchoring systems are available for bolt-in, built-in or bonded in installations for various wall constructions.

The UL fire rated options outlined in the chart below have been successfully tested in accordance with UL 9 and UBC 7-4 (1997) for a 4-sided single window configuration.

All of our fixed window systems are available in 3 standard and 24 optional pre-matched colors with custom color matching available.

Please contact Tiger with your specific fixed window product requirements or visit our website, [www.tigerdoor.com](http://www.tigerdoor.com).



## FIRE RATED OPTIONS

Hourly Fire Ratings: Up to 1-1/2 hours with UL approved ceramic glazing material.  
Up to 3/4 hours with UL approved wire glass glazing material.

Max. Exposed Glass Area: 2353 sq. inches with UL approved ceramic glazing material.  
1296 sq. inches with UL approved wire glass glazing material.  
Maximum width of exposed glass: 43"  
Maximum width of exposed glass: 54-3/4"

Frame Profile Limitations: Face trims from 1" to 4" Jamb depths to 13-1/2"

Frame Anchorage: Bolt-in or built-in masonry or poured concrete walls.



P.O. Box 70, 574 West Otterman Street  
Greensburg, PA 15601-0070 U.S.A.  
Tel: 724-834-7300; 1-800-979-7300

Fax: 724-830-2871  
E-mail: [info@tigerdoor.com](mailto:info@tigerdoor.com)  
Web: [www.tigerdoor.com](http://www.tigerdoor.com)